


[About](#)
[Vision](#)
[Products](#)
[Support](#)

פד"מ-טק (1991) בע"מ

מיקל סטורץ' | 02.583.2511

PaZaM-tech@pobox.com

www.PaZaM-tech.co.il



# PIXCI® ECB2

## ExpressCard - Notebook Dual Base Camera Link Frame Grabber

[Selection Guide](#)
[Manual](#)
[Pricing](#)

### Software

[XCAP](#)
[XCLIB](#)
[PXIPL](#)

### The PIXCI® ECB2 frame grabber

provides two interfaces for any two Base camera link cameras. The PIXCI ECB2 is handled by EPIX' software as if two PIXCI ECB1 boards are installed. The ECB2 will accept two trigger signals one for each camera; or allows a single trigger to control capture from both cameras.

A strobe output signal is generated for each trigger. The PIXCI ECB2 frame grabber supports two cameras with a combined sustained bandwidth up to 204 MB/second. Compatible with **ExpressCard**, the mobile PCI Express interface for notebook computers, the PIXCI® ECB2 frame grabber interfaces to more than 100 of the newest, most advanced, highest bandwidth machine vision cameras available.



### The PIXCI® ECB2 offers:

- 191 megabytes per second, sustained, data transfer rate to laptop. Faster notebooks may provide up to 204 megabytes per second, sustained, data rates. Burst transfers at 250 megabytes per second.
- Camera specific controls - exposure, bit depth, gain, frame rate, etc.
- Camera operation in free-run mode for maximum frame rate capture.
- Camera operation in control (trigger) mode.
- \$645 with XCAP-Lite imaging program.
- Dual Base Configuration Camera Link Frame Grabber
- ExpressCard Compatible
- 250 Megabyte/sec Burst Transfers
- Line Scan or Area Scan
- Camera Frame Rate Sequence Capture
- Triggered Image Sequence Capture
- 64-Bit Memory Addressing
- Camera Integration & Async Reset Control
- Integration From Microseconds to Minutes
- Images Stored in Motherboard Memory or directly to hard drive
- Compatible with 32 / 64-bit Windows & Linux
- RoHS Compliant

The **PIXCI® ECB2** is a plug-n-play frame grabber requiring no hardware setup or adjustment. Install the board, load the software, connect the camera, and capture images. Upon startup, the XCAP imaging program reads a camera identification chip on the PIXCI® ECB2 frame grabber, allowing XCAP to load the appropriate video format and display the camera's dedicated Capture & Adjust Dialog.

The **XCAP** imaging program offers video-to-disk capture subject to the performance of the notebook's hard drive. Capture 1600 x 1200 Bayer pattern color images, 14 frames per second, 8 bits per pixel, directly to notebook hard drive for 2 hours!

**Interfaces to almost any base camera link camera.** The PIXCI® ECB2 frame grabber requires a computer with an **ExpressCard/54** slot. Few cameras exceed the frame grabber's 191 megabyte per second sustained data rate. Support for medium or full camera link cameras in a notebook is available with the [PIXCI® EC1](#). Support for higher bandwidth camera link cameras is available with the [PIXCI® E4](#) frame grabber in a desktop computer with a x4 PCI Express bus. The PIXCI® E4 interfaces to cameras with a bandwidth requirement up to 700 Megabytes (5600 Mbits) per second.



**Solutions and Support:**

EPIX, Inc. has been providing imaging solutions and support for OEM machine vision manufacturers and engineers since 1984. EPIX, Inc. assembles complete imaging systems with cameras, frame grabbers, and high-performance notebook computers. EPIX imaging systems, custom-built to your specifications, typically feature Intel motherboards and processors. Contact EPIX, Inc., or an authorized distributor of EPIX® imaging products, for help selecting cameras, frame grabbers, imaging software, optics, and computer systems.

**Featured In:****Notebook Compatibility:**

The PIXCI® ECB2 frame grabber requires a notebook with ExpressCard/54 slot. When purchasing a notebook, ask the computer supplier for their return policy. Plan the purchase to coincide with the purchase of the PIXCI® ECB2 and camera. Allow a few days to complete testing and for returning the notebook if it proves incompatible.

The PIXCI® ECB2 frame grabber always ships with a version of the XCAP program -- either XCAP-Lite (no charge) XCAP-Ltd, or XCAP-Std. XCAP provides camera control, image display, image capture, pixel examination and image save – everything required to immediately test and verify compatibility without the need for software development.

Install the XCAP program, the PIXCI® ECB2 frame grabber, and the targeted camera to verify that all work properly together. Operate the camera at maximum frame rate, resolution, and bit depth. Contact EPIX® technical support, or your distributor of EPIX® imaging products, with any questions.

If the notebook proves incompatible, then please report the incompatibility to either EPIX, Inc., or to your distributor of EPIX® imaging products. We can extend the evaluation period to allow compatibility verification with another notebook.

HP/Compaq, Toshiba, Lenovo, Eurocom and Intel Whitebox Notebooks have been tested and are recommended. Dell notebooks equipped with an Intel 915 chipset are recommended. Dell notebooks equipped with an Intel 945 chipset are not recommended. Update: Customers are reporting Dell notebooks working after updating the BIOS.

[Notebooks tested with the PIXCI® EC1.](#)

**PRICING**

**PIXCI® ECB2** - Notebook ExpressCard/54 Interface for Camera Link cameras.

- |                                  |       |   |   |          |
|----------------------------------|-------|---|---|----------|
| <input checked="" type="radio"/> | ECB2- | <input type="text" value="Model/Order Code"/> | Enter your camera model or the specific order code from the <a href="#">full price list</a> for customized default camera controls. Boards ordered with customized controls may still be used with other Camera Link cameras. | \$645.00 |
| <input type="radio"/>            | ECB2- | GENERIC                                       | Defaults to generic Camera Link controls. Customized controls may be selected for supported camera models.  | \$645.00 |

**Camera Link Cable**

<input type="text" value="CBL-MCL-1M"/>	MiniCL to CL Data cable for Camera Link, 1 meter	\$110.00
---	--	----------

**XCAP Imaging Application Software** - [Detailed version information.](#)

- |                                  |       |      |   |              |
|----------------------------------|-------|------|---|--------------|
| <input checked="" type="radio"/> | XCAP- | LITE | Provided with purchase of any PIXCI® imaging board. Limited to 64MB frame buffer.                               | \$ No Charge |
| <input type="radio"/>            | XCAP- | LTD  | Adds support for up to 4 GB frame buffer or 8GB on 64 bit operating systems and <a href="#">other features.</a> | \$495.00     |
| <input type="radio"/>            | XCAP- | STD  | All image processing functions available, video to disk, and <a href="#">other features.</a>                    | \$1495.00    |

**Programming Libraries** - Single Developer, Royalty-Free Licenses. See the [XCLIB](#) and [PXIPL](#) product pages for details.

- XCLIBLITE- WNT (XCLIB-Lite for Windows NT, 2000, XP, Vista, 7 32 bit DLL) Limited \$195.00  
to one board, 64MB RAM, 32-bit Windows.
- XCLIB- WNT (XCLIB for or Windows NT, 2000, XP, Vista, 7 32 bit DLL) Full \$495.00  
library for interacting with all PIXCI® boards.
- XCLIBIPL- WNT (XCLIB w. PXIPL for Windows NT, 2000, XP, Vista, 7 32 bit DLL) \$995.00  
Adds optional PXIPL image processing and analysis library.
- No Library

**Request More Information:**

Name:

Email:

Questions, comments, requirements?

All prices F.O.B. Buffalo Grove, Illinois.  
USA Terms: Net 30 Days, subject to credit acceptance.  
Contact EPIX Inc., or your distributor of EPIX® imaging products, for volume discounts and OEM pricing.

EPIX, SILICON VIDEO, and PIXCI are registered trademarks of EPIX, Inc. XCAP, XCIP, XCLIB, and PXIPL are trademarks of EPIX, Inc. Other brand, product, and company names are trademarks or registered trademarks of their respective owners. Prices, terms, and specifications subject to change without notice.

EPIX® imaging products are not authorized for use as critical components in life support devices or systems without the express written approval of the president of EPIX, Inc.

Software price protection: Within 90 days of original shipment, a discount equal to the original purchase price of XCAP, XCIP, XCLIB, or XCLIB+PXIPL may be applied to a new version of the same software.

Programming libraries license a single program developer; the developed program may be reproduced without payment of royalties, as detailed in the Software License Agreement.

[Back to EPIX Products](#)

[Back to the EPIX home page](#)

### Image Processing Products For Research and Industry

Specifications and prices subject to change without notice.

EPIX® imaging products are made in the USA.

EPIX, SILICON VIDEO, and PIXCI are registered trademarks of EPIX, Inc. 4MIP, SVIP, XCIP, XCAP, 4MEG VIDEO, 1MEG VIDEO, SILICON VIDEO MUX, QUICK SET VIDEO, 12-7 MUX, IMAGE MEMORY EXPANSION, COC40, COC402, CL3SD, 4MOBJ, SVOBJ, XCOBJ, XCLIB, PXIPL, and XCLIBIPL are trademarks of EPIX, Inc. Other brand, product, and company names are trademarks or registered trademarks of their respective owners.

Copyright © 2010 EPIX, Inc. All rights reserved.

Modified:  
17-Nov-2009

פד"מ-טק (1991) בע"מ

מייקל סטורץ' | 02.583.2511

PaZaM-tech@pobox.com

www.PaZaM-tech.co.il